



# Product Data Sheet

## Benzoic Acid

Version 2

Technical Grade, Flake

Revision 06/26/2017

**Benzoic acid flake is a mono-functional aromatic acid. It is an intermediate utilized in the synthesis of salts and esters. Benzoic acid is also used as a building block for alkyd resins, and an aid in oil well recovery, a component of antifreeze and a preservative.**

### SPECIFICATIONS

Appearance	White flakes/powder
Assay	99.5% min
Color, APHA	50 max
Moisture	0.1% max
Residue (ash) on ignition	0.1% max

### TYPICAL PROPERTIES

Arsenic (As)	≤ 1 ppm
Biphenyl impurities	≤ 0.25 %
Boiling Point @ 760 mm Hg	249 °C
Cadmium	≤ 1 ppm
Chlorine Compounds (as Cl)	≤ 0.02 %
Cobalt (Co)	≤ 1 ppm
Flash Point, CC	121.9 °C
Heavy Metals (as Pb)	≤ 10 ppm
Lead (Pb)	≤ 1 ppm
Manganese (Mn)	≤ 1 ppm
Melting/Freezing Point	121 – 125 °C
Mercury (Hg)	≤ 0.5 ppm
Molecular weight	122.12

Before using this product, you must become completely familiar with the safety and hazard information contained in the material safety data sheet. Velsicol Chemical LLC (the seller) presents this data sheet information, to the best of our knowledge, to be true and accurate without warranty and disclaims any liability arising from its use and /or misuse. Seller recommends use of the information to make your own determination of its suitability and completeness for your own use in commercial processes which do not violate third-party patent rights or any laws or regulations. The seller makes no warranties, express or implied, including, but not limited to the implied warranties of merchantability and fitness for a particular purpose except as expressly stated in the Seller's conditions of sale or sales acknowledgement form.



# Product Data Sheet

## Benzoic Acid

### Technical Grade, Flake

---

#### TYPICAL PROPERTIES *(continue)*

Odor	Slightly aromatic
Phenols	≤ 10 ppm
Phthalic acid and phthalic anhydride	≤ 0.5%
Specific Gravity @ 20°C	1.321
Sulfur compounds (as S)	≤ 0.002%
Vapor pressure, @20°C	0.0011 hPa
Zinc	≤ 25 ppm

#### REGULATORY INFORMATION

CAS Registration Numbers:	65-85-0
EINECS Numbers:	200-618-2

#### CONTACT INFORMATION

**Customer Service** **1-877-847-8351**  
**Velsicol Chemical LLC**  
**10400 W Higgins Road, Suite 303, Rosemont, IL 60018**  
**[www.Velsicol.com](http://www.Velsicol.com)**

06/2017

Before using this product, you must become completely familiar with the safety and hazard information contained in the material safety data sheet. Velsicol Chemical LLC (the seller) presents this data sheet information, to the best of our knowledge, to be true and accurate without warranty and disclaims any liability arising from its use and /or misuse. Seller recommends use of the information to make your own determination of its suitability and completeness for your own use in commercial processes which do not violate third-party patent rights or any laws or regulations. The seller makes no warranties, express or implied, including, but not limited to the implied warranties of merchantability and fitness for a particular purpose except as expressly stated in the Seller's conditions of sale or sales acknowledgement form.