



VELSIFLEX™ MATERIAL SELECTION GUIDE

MARKET APPLICATIONS

Version 2, Revision 06/26/2017

Non-PVC

VELSIFLEX™ ESTERS

	320	328	342	342S
Adhesives				
Polyvinyl Acetate Latex	●	●	●	
Caulks & Sealants				
Latex Acrylic	●	●	●	
Vinyl Acrylic	●	●	●	
Polysulphide			●	●
Polyurethane			●	●
Coatings				
Latex	●	●	●	
Lacquers			●	
Powders			●	
Inks				
C Gravure			●	
Castable Polyurethane				●
Flexible PVC				
Flooring			●	●
Plastisols	●	●	●	
Sealants	●	●	●	
Foam	●	●	●	
KEY PROPERTIES				
Wet tack, quick grab	●	●	●	
Open time	●	●	●	
Set time	●	●	●	
Adhesion	●	●	●	
Solvator	●	●	●	
Viscosity Modifier	●	●	●	
Softening agent	●	●	●	●
Coalescing agent			●	
Processibility			●	
Low temp flexibility	●	●	●	
Stain resistance	●	●	●	
Solvent resistance	●	●	●	
Oil resistance	●	●	●	
UV resistance	●	●	●	
FDA approved	●	●	●	●